Solar Label Value Pack

The HellermannTyton Solar Label Value Pack contains an assortment of the labels required for NEC 2017 code compliance. All labels are made from UV stable vinyl and dye-based inks and protected by a weather-resistant laminate. A permanent adhesive adds to their lasting performance. This label kit is a convenient, low-cost solution for helping to ensure your solar installation passes inspection.

Solar Label Value Pack Contents:

Size: 1" x 6.5" • Qty: 6

WARNING: PHOTOVOLTAIC POWER SOURCE


Size: 1" x 6.5" • **Qty:** 1

DO NOT DISCONNECT **UNDER LOAD**

Size: 4" x 6" • Qty: 1

SOLAR PV SYSTEM EQUIPPED WITH RAPID SHUTDOWN

TURN RAPID SHUTDOWN **SWITCH TO THE"OFF"** POSITION, TO SHUTDOWN CONDUCTORS OUTSIDE THE ARRAY. **CONDUCTORS WITHIN ARRAY REMAIN ENERGIZED IN SUNLIGHT**



Size: 1.75" x 5.5" • **Qty:** 1

PHOTOVOLTAIC SYSTEM **EQUIPPED WITH** RAPID SHUTDOWN

Size: 1" x 3.75" • **Qty:** 1

PHOTOVOLTAIC

DC DISCONNECT

Size: 1" x 3.75" • Qty: 1

PHOTOVOLTAIC

AC DISCONNECT

Size: 1" x 4" • Qty: 2

DC JUNCTION BOX

Size: 1" x 4" • Qty: 1

kWh METER

Features and Benefits

- The most complete collection of required PV labels in one package, saving you time with one-order simplicity.
- ALL labels are NEC 2017 compliant, eliminating guesswork and the risk of a failed inspection due to nonconforming labeling.
- Long-lasting, permanent adhesive ensures high-performance results on a variety of metals, paints and man-made materials.

Size: 1" x 6.5" • **Qty:** 1

RAPID SHUTDOWN SWITCH FOR SOLAR PV SYSTEM


Size: 1" x 5" • Qty: 2

DC PHOTOVOLTAIC **SOURCE CIRCUIT**

Size: 4" x 6" • Qty: 1

SOLAR PV SYSTEM EQUIPPED WITH RAPID SHUTDOWN

TURN RAPID SHUTDOWN SWITCH TO THE "OFF" POSITION TO SHUT DOWN PV SYSTEM AND REDUCE SHOCK HAZARD IN THE ARRAY



Size: 1.75" x 5.5" • **Qty:** 1

MAIN PHOTOVOLTAIC **SYSTEM AC DISCONNECT**

Size: 1" x 4" • Qty: 1

DC COMBINER BOX

Size: 1" x 4" • Qty: 1

CAUTION: DO NOT INSTALL ADDITIONAL LOADS IN THIS PANEL **Size:** 2" x 4.125" • **Qty:** 1

A WARNING

ELECTRICAL SHOCK HAZARD

IF A GROUND FAULT IS INDICATED

NORMALLY GROUNDED CONDUCTORS

MAY BE UNGROUNDED AND ENERGIZED

Size: 2" x 4.125" • **Qty:** 1

A WARNING

ELECTRICAL SHOCK HAZARD

THE DC CONDUCTORS OF THIS
PHOTOVOLTAIC SYSTEM ARE UNGROUNDED
AND MAY BE ENERGIZED

Size: 2" x 4" • Qty: 1

AWARNING

THIS SERVICE METER
IS ALSO SERVED BY A
PHOTOVOLTAIC SYSTEM

Size: 1" x 3.75" • **Qty:** 1

PHOTOVOLTAIC AC DISCONNECT

MAXIMUM AC OPERATING CURRENT: NOMINAL OPERATING AC VOLTAGE:

Size: 1.75" x 3.75" • **Qty:** 2

MAXIMUM VOLTAGE
MAXIMUM CIRCUIT CURRENT

MAX RATED OUTPUT CURRENT OF THE CHARGE CONTROLLER OR DC-TO-DC CONVERTER (IF INSTALLED) **Size:** 2" x 4" • **Qty:** 1

A WARNING

THIS EQUIPMENT FED BY
MULTIPLE SOURCES:
TOTAL RATING OF ALL OVERCURRENT
DEVICES EXCLUDING MAIN POWER
SUPPLY SHALL NOT EXCEED
AMPACITY OF BUSBAR

Size: 2" x 4" • **Qty:** 2

A WARNING

DUAL POWER SUPPLY

SOURCES: UTILITY GRID AND PV SOLAR ELECTRIC SYSTEM

Size: 2" x 3.75" • **Qty:** 2

A WARNING

ELECTRICAL SHOCK HAZARD

TERMINALS ON THE LINE AND LOAD SIDES MAY BE ENERGIZED IN THE OPEN POSITION

Size: 1" x 6.5" • **Qty:** 4

CAUTION: SOLAR CIRCUIT

Size: 1" x 6.5" • **Qty:** 1

CAUTION: SOLAR ELECTRIC SYSTEM CONNECTED

Size: 1" x 4" • Qty: 1

AWARNING

PV SOURCE CIRCUIT

Size: 1" x 4" • Qty: 1

ACAUTION

INVERTER INPUT CIRCUIT

Size: .75" x 4.125" • **Qty:** 3

A WARNING

POWER SOURCE OUTPUT CONNECTION.
DO NOT RELOCATE THIS OVERCURRENT DEVICE.

Size: .75" x 4.125" • **Qty:** 2

ACAUTION

PHOTOVOLTAIC SYSTEM CIRCUIT IS BACKFED

Size: 3.75" x 5" • **Qty:** 1

CIRCUIT 1	CIRCUIT 1	CIRCUIT 1
CIRCUIT 1	CIRCUIT 1	CIRCUIT 1
CIRCUIT 2	CIRCUIT 2	CIRCUIT 2
CIRCUIT 2	CIRCUIT 2	CIRCUIT 2
CIRCUIT 3	CIRCUIT 3	CIRCUIT 3
CIRCUIT 3	CIRCUIT 3	CIRCUIT 3
CIRCUIT 4	CIRCUIT 4	CIRCUIT 4
CIRCUIT 4	CIRCUIT 4	CIRCUIT 4
CIRCUIT 5	CIRCUIT 5	CIRCUIT 5
CIRCUIT 5	CIRCUIT 5	CIRCUIT 5

HellermannTyton

HellermannTyton North American Corporate Headquarters

7930 N. Faulkner Rd, PO Box 245017 Milwaukee, WI 53224-9517 Phone: (414) 355-1130, (800) 537-1512

Fax: (414) 355-7341, (800) 848-9866 email: corp@htamericas.com www.hellermann.tyton.com

IATF 16949, ISO 9001, and ISO 14001 Certified

HellermannTyton Canada

Unit #4, 205 Industrial Parkway North Aurora, Ontario L4G 4C4 Canada Phone: (800) 661-2461 Fax: (800) 390-3904

email: sales@hellermanntyton.ca

HellermannTyton Mexico

Anillo Periferico Sur 7980 Edificio 6A Parque Industrial Tecnologico II Santa María Tequepexpan Tlaquepaque, Jalisco, Mexico 45601 Phone: 011-52-33-3-133-9880 Fax: 011-52-33-3-133-9861 email: info@hellermanntyton.com.mx

ISO 9001 Certified

Warranty Policy HellermannTyton products are warranted to be free from defects in material and workmanship at the time sold by us; but our obligation under this warranty and that of the seller is limited to the replacement of the product, and neither we nor the seller are bound by any other warranty, expressed, implied or statutory. Under no circumstances are we or the seller liable for any loss, damage, expenses or consequential damages of any kind arising out of the use or inability to use these products. All are sold with the understanding that the user will test them in actual use and determine their adaptability for the intended uses.