



# SNA-NB-US 6000

- 240V/120V Output
- Off-grid seamless switching
- Split phase/Unbalanced 3-Phase
- Support up to 16pcs in parallel
- Host inverter automatically generated to manage the entire system
- Separate generator port available



Generator  
compatible



Monitoring  
control



Warranty



On/off  
seamless  
switch



Your Reliable Energy Solution Partner

# Specification

INPUT (PV DC)		SNA-NB-US 6000
Max. PV array power (W)		8000(4000/4000)
Rated PV input voltage(V)		320
Number of independent MPPT inputs		2
PV input voltage range(V)		100~480
MPPT voltage range(V)		120~385
Start-up voltage(V)		100
Max. PV input current per MPPT(A)		17/17
Max. PV short-circuit current input per MPPT(A)		25/25
Battery		
Compatible battery type		Lithium-ion/Lead-Acid
Rated battery voltage(V)		48
Battery voltage range(V)		38.4~60
Max. charging/discharging current(A)		125/140
Max. charging/discharging power(W)		6000
Recommend max. capacity of battery per inverter		>200AH
Force wake up battery from PV function		YES
Force wake up battery from Grid function		YES
Grid		
Rated AC voltage(V)		110(L-N)/220(L <sub>1</sub> -L <sub>2</sub> ); 120(L-N)/240(L <sub>1</sub> -L <sub>2</sub> )
Rated AC frequency(Hz)		50/60
Max. AC input current(A)		41A@220V/37.5A@240V
Max. AC input power(W)		9000
Rated AC current of BYPASS relays(A)		50
GEN		
Rated GEN voltage(V)		230
Rated GEN frequency(Hz)		50/60
Rated GEN input current(A)		32
Rated GEN input power(W)		7370
Rated GEN current of BYPASS relays(A)		60
UPS		
Rated output power(W)		6000
Rated output voltage(V)		110/220; 120/240
Rated output current(A)		28A@220V/25A@240V
Rated output frequency(Hz)		50/60
Surge power, duration		2Pn, <2S
Switching time		<15ms @ Single/ <30ms @ Parallel
Wave form		Sine wave
THDV		<3%
Efficiency		
Max. MPPT efficiency		99.0%
Max. efficiency		93.0%
Max. charging/discharging efficiency		93.0%
Protection		
Over current/voltage protection(Y/N)		YES
AC short-circuit current protection(Y/N)		YES
Grid monitoring(Y/N)		YES
AC Surge protection Type III		YES
Battery reverse polarity protection(Y/N)		YES
General		
Dimensions(W*H*D)		450*650*150mm/17.7*25.6*5.9inch
Weight		14.5kg/33.1lbs
Ingress protection rating		IP20
Operating environment temperature range		0~50°C
Storage temperature range		-15~60°C
Relative humidity		5%~95%
Display & Communication interface		LCD+LED, RS485/Wi-Fi/CAN
Warranty		2 years
Cooling method		Smart Cooling
Topology		Transformer-less
Altitude		<2000m
Noise emission(typical)		<50dB
Standard & Certification		

FCC Part15B, UL 1741:2021 Ed.3, CSA C22.2#107.1:2016 Ed.4+U1