

# Product data sheet

## Characteristics

### HEPD80

SPD, HEPD type 1, 120/240 V, 1 PH, 3 wire, 80 kA

Product availability: Stock - Normally stocked in distribution facility



#### Main

Product	Surge protection device
Range	Square D
Device Short Name	HEPD

#### Complementary

Surge Current	80 kA per phase
System Voltage	120/240 V AC
Phase	1 phase
Wiring Configuration	3-wire (isolated ground)
MCOV	150 V
Line Rated Current	10 kA
SCCR	25 kA
Local Signalling	1 LED, green = normal operation
Input voltage	600 V L - N terminal(s) 600 V L - G terminal(s) 1000 V L - L terminal(s) 900 V N - G terminal(s)
Height	3.23 in
Width	3.72 in
Depth	2.1 in

#### Environment

Enclosure Rating	NEMA 4X
Standards	UL 1449 CUL UL 1449 type I ed. 4
Ambient Operating	-31...149 °F (-35...65 °C)

#### Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	00785901008729
Nbr. of units in pkg.	1
Package weight(Lbs)	1.2
Returnability	Y
Country of origin	US

#### Offer Sustainability

California proposition 65

WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---