



Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|------------------------------|---|
| Product | Miniature circuit-breaker |
| Range | Homeline |
| Line Rated Current | 20 A |
| Certifications | UL listed |
| System Voltage | 120/240 V AC |
| Mounting Type | Plug-in |
| Number of Poles | 2P |
| Short Circuit Current Rating | 10 kA |
| Number of Spaces | 2 |
| Circuit Breaker Type | Standard |
| Ratings | HACR rated |
| Electrical Connection | Clamp terminal for 2 cables |
| Wire Size | AWG 14...AWG 8 for 1 cable(s) (aluminium/copper) AWG 14...AWG 10 for 2 cable(s) (copper) |
| Height | 3.13 in |
| Width | 2 in |
| Depth | 2.98 in |


Environment

| | |
|---------------------------------------|----------------|
| Ambient air temperature for operation | 104 °F (40 °C) |
|---------------------------------------|----------------|

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 00046 - HOM/T 15-30A 1P; 15-60A 2P |
| Discount Schedule | DE3D |
| GTIN | 00785901065289 |
| Nbr. of units in pkg. | 5 |
| Package weight(Lbs) | 0.650000000000000002 |
| Returnability | Y |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1323 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|----------|
| Warranty period | Lifetime |
|-----------------|----------|