

# Product data sheet

## Characteristics

# HOMT1515220

## MINIATURE CIRCUIT BREAKER 120/240V

### 15A



Product availability: Stock - Normally stocked in distribution facility



#### Main

Product	Miniature circuit-breaker
Range	Homeline
Line Rated Current	20 A 15 A
Certifications	UL listed
System Voltage	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P 1P
Short Circuit Current Rating	10 kA
Number of Spaces	2
Circuit Breaker Type	Quad tandem
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	AWG 14...AWG 8 for 1 cable(s) (aluminium/copper)
Height	3.13 in
Width	2 in
Depth	2.98 in

#### Environment

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

#### Ordering and shipping details

Category	00046 - HOM/T 15-30A 1P; 15-60A 2P
Discount Schedule	DE3D
GTIN	00785901101000
Nbr. of units in pkg.	5
Package weight(Lbs)	0.8399999999999997
Returnability	Y
Country of origin	MX

#### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

#### Contractual warranty

Warranty period	Lifetime
-----------------	----------