



### Main

Product or component-type	Miniature circuit-breaker
Range of product	Homeline
Line Rated Current	200 A
Product certifications	UL listed
System Voltage	120/240 V AC
Mounting mode	Plug-in
Poles description	2P
Short-circuit current	10 kA
Number of spaces required	4
Circuit breaker type	Standard
Circuit breaker application	HACR rated
Electrical connection	Box lugs
AWG gauge	AWG 4...300 kcmil for 1 cable(s) (aluminium/copper)

### Environment

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

### Ordering and shipping details

Category	00144 - HOM BREAKERS 150-200A
Discount Schedule	DE3D
GTIN	00785901876601
Nbr. of units in pkg.	1
Package weight(Lbs)	3.0600000000000001
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity <a href="#">Schneider-Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

---

Warranty period	Lifetime
-----------------	----------

---

Product Life Status : Commercialised