

Product availability: Stock - Normally stocked in distribution facility



### Main

Product	Miniature circuit-breaker
Range	Homeline
Line Rated Current	30 A
Certifications	UL listed
System Voltage	120/240 V AC
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2
Circuit Breaker Type	Quad tandem
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	AWG 14...AWG 8 for 1 cable(s) (aluminium/copper)
Height	3.13 in
Width	1.97 in
Depth	3.23 in
Tightening torque	4...4.6 N.m for 2.5...10 mm <sup>2</sup> (AWG 14...AWG 6) 4...4.6 N.m for 2.5...20 mm <sup>2</sup> (AWG 12...AWG 6)

### Environment

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

### Ordering and shipping details

Category	00046 - HOM/T 15-30A 1P; 15-60A 2P
Discount Schedule	DE3D
GTIN	00785901970453
Nbr. of units in pkg.	5
Package weight(Lbs)	1
Returnability	Y
Country of origin	MX

### Contractual warranty

Warranty period	Miniature Breaker - Homeline - Quad - 120/240V - 10kA - 30/30A - UL Listed
-----------------	--