

# Product data sheet

## Characteristics

# HOM3060L225PRB

## HOM OUTD 225A MLO 30/60CIR



### Main

Product or component-type	Load Center
Range of product	Homeline
Load center type	Main lugs
Line Rated Current	225 A
Number of spaces	30
Number of circuits	60
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Electrical connection	Lugs

### Complementary

Short-circuit current	10 kA
Number of tandem circuit breakers	30
Phase	1 phase
System Voltage	120/240 V AC
AWG gauge	AWG 4...300 kcmil (aluminium) AWG 4...250 kcmil (copper)
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Material	Tin plated aluminium busbar
Enclosure material	Welded galvannealed steel
Surface finish	Baked enamel grey
Box number	7R

### Environment

Product certifications	UL E-6294
------------------------	-----------

### Ordering and shipping details

Category	00145 - HOM LC&CVR,12-42CKT NEMA3R
Discount Schedule	DE3C
GTIN	00785901977490
Nbr. of units in pkg.	1
Package weight(Lbs)	36.89999999999999
Returnability	Y
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity <a href="#">Schneider-Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Product Life Status : **Commercialised**